

NPS52-86-004

NAVAL POSTGRADUATE SCHOOL

Monterey, California



EXPERIENCE WITH Ω

*IMPLEMENTATION OF A
PROTOTYPE PROGRAMMING ENVIRONMENT
PART III*

Bruce J. MacLennan
//

January 1986

Approved for public release; distribution unlimited

Prepared for:

FedDocs
D 208.14/2
NPS-52-86-004

Chief of Naval Research
Arlington, VA 22217

Fed 6012
D 207 14/2
MPC-55-86-004

NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral R. H. Shumaker
Superintendent

D. A. Schrady
Provost

The work reported herein was supported by Contract from the
Office of Naval Research.

Reproduction of all or part of this report is authorized.

This report was prepared by:

VINCENT Y. LUM/
Chairman
Department of Computer Science

KNEALE T. MARSHALL
Dean of Information and
Policy Science

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER NPS52-86-004	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) EXPERIENCE WITH Ω IMPLEMENTATION OF A PROTOTYPE PROGRAMMING ENVIRONMENT PART III		5. TYPE OF REPORT & PERIOD COVERED	
		6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) Bruce J. MacLennan		8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93943-5100		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61153N; RR014-08-01 N0001485WR24057	
11. CONTROLLING OFFICE NAME AND ADDRESS Chief of Naval Research Arlington, VA 22217		12. REPORT DATE January 1986	
		13. NUMBER OF PAGES 46	
14. MONITORING AGENCY NAME & ADDRESS (If different from Controlling Office)		15. SECURITY CLASS. (of this report)	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This is the third report of a series exploring the use of the Ω program- ming notation to prototype a programming environment. This environment includes an interpreter, unparser, syntax directed editor, command interpreter, debugger and code generator, and supports programming in a small applicative language. The present report extends the interpreter, unparser, syntax directed editor, command interpreter and debugger to accommodate comments (which are used both statically and dynamically) and conditional expressions. A running implemen- tation of these ideas is listed in the appendices.			

EXPERIENCE WITH Ω
IMPLEMENTATION OF A
PROTOTYPE PROGRAMMING ENVIRONMENT

PART III

Bruce J. MacLennan
Computer Science Department
Naval Postgraduate School
Monterey, CA 93943

Abstract:

This is the third report of a series exploring the use of the Ω programming notation to prototype a programming environment. This environment includes an interpreter, unparser, syntax directed editor, command interpreter, debugger and code generator, and supports programming in a small applicative language. The present report extends the interpreter, unparser, syntax directed editor, command interpreter and debugger to accommodate comments (which are used both statically and dynamically) and conditional expressions. A running implementation of these ideas is listed in the appendices.

1. Introduction

Our goal in this series of reports* [MacLennan85b, MacLennan85c] is to explore in the context of a very simple language the use of the Ω programming notation [MacLennan83, MacLennan85a] to implement some of the tools that constitute a programming environment.

The structure of this report is as follows: First we discuss the accommodation of comments in the abstract structure of the program. This demonstrates how documentation and nonprogram text can be incorporated into the program structure. These comments are used both statically (i.e., as commentary in the source code) and dynamically (i.e., to provide informative information at runtime). Second we introduce a conditional expression into the language. This involves no new ideas, but is essential if the recursive functions introduced in Part IV are to be useful.

* Support for this research was provided by the Office of Naval Research under contract N00014-86-WR-24092.

2. Comments

2.1 Requirements

How can we include comments in our programs? In particular, how can comments be incorporated into the abstract program structure? The solution to this problem will indicate the solution to a more general problem, namely, how documentation, specifications, explanations, etc. can be related to the program structure.

Our solution here is to define a new relation 'Comment' that is used to link a comment to any program node. Its properties are:

- `Comment (S, E)`
 S is the comment on E
- `Degree (Comment, 2)`
- `Function (Comment, expr, string)`

The following transcript is an example of creating and displaying comments:

show

```
let X = (3+5)
let Y = (6÷2)
(X+ (Y-1)) ]
```

rem "Distance"

show

```
let {Distance}
X = (3+5)
let Y = (6÷2)
(X+ (Y-1)) ]
```

Notice that the comment "Distance" is attached to the current node (a **let** in this case), and that this alters the formatting of that node. The presumption is that the comment on a **let** documents the name defined by that **let**. Next we move to the inner **let** and attach a comment to it:

in

[let Y = (6÷2)

(X+ (Y-1))]

rem "Altitude"

Comments can also be attached to operator application nodes, as the following illustrate:

in

(X+ (Y-1))

in

X

next

(Y-1)

rem "offset"

root

let {Distance}

X = (3+ 5)

let {Altitude}

Y = (6÷2)

(X+ {offset}{Y-1})]]

2.2 Editor Commands

The **rem** command, which attaches a comment to a program node, is straight-forward to implement:

*Command(**rem**), *Argument(*S*), CurrentNode(*E*), ¬Comment(− ,*E*)

⇒ Comment(*S*,*E*).

*Command(**rem**), *Argument(−), CurrentNode(*E*), Comment(− ,*E*)

⇒ Display("node already commented").

Note that we allow only one comment to be attached to a node. This is a debatable restriction, but it seems that permitting multiple comments would require some strategy for organizing them. This is left

as an exercise for the reader.

We also need a `delete_rem` command for uncommenting a node:

```
*Command(delete_rem, CurrentNode(E), *Comment(-,E)
```

```
⇒ Display("done").
```

```
*Command(delete_rem, CurrentNode(E), -Comment(-,E)
```

```
⇒ Display("no comment").
```

2.3 Unparsing Comments

Unfortunately, with our present organization, most of the unparsing rules must be modified to incorporate comments into the unparsed program representation. Is there a way of unparsing comments without duplicating all the unparsing rules? This is left as an exercise for the reader.

First we consider the rule for unparsing comments on operator applications. Our goal is that an addition node with a comment be displayed like this:

$$\{S\} (X + Y)$$

This is easily accomplished by the rule:

```
Appl(E), Op(N,E), Left(X,E), Right(Y,E), *Image(U,X), *Image(V,Y), Comment(S,E)
```

```
⇒ Image("{ " ^ S ^ " } ( " ^ U ^ N ^ V ^ " ) ", E)
```

else previous Appl rule.

The only difference from the uncommented case is the incorporation of the comment into the image.

Unparsing comments on Vars and Cons is done in essentially the same way as those on Appls.

Next we consider unparsing comments on blocks. The goal is a display of the form:

```
{let {S}
```

```
N = X
```

```
B
```

Again, all we have to do is provide an unparsing rule like the uncommented one, except that the

comment is incorporated in the image:

Block(E), BndVar(N, E), BndVal(X, E), Body(B, E),

*Image(U, X), *Image(V, B), Comment(S, E)

\Rightarrow Image(

TabIn ^NL ^“{let {” ^ S ^“}”

^ TabIn ^NL ^ N ^“ = ” U

^NL ^ V ^“ ”

^ TabOut ^ TabOut, E)

else previous rule.

2.4 Dynamic Use of Comments

Since a comment on a block presumably describes the purpose of the local variable, it would be convenient to include this comment in the dynamic context, so that it can be displayed by the debugger. This is accomplished by modifying the evaluator so that the comment on a block is incorporated in the context (by being attached as a ‘Comment’ to the context). The rule that does this is:

Block(E), BndVar(N, E), BndVal(X, E), Body(B, E), *Value(V, X, C), *Avail(D), Comment(S, E)

\Rightarrow Context(D), Binds(D, N, V), Nonlocals(C, D), Eval(B, D), Comment(S, D)

else previous rule.

There is no point in making comments part of the dynamic structure unless we are going to make use of them. For example, we can modify the debugger so that it displays any comments attached to a binding, so that we will know the purpose of the variable. Here is an example transcript that makes use of the example program shown above:

context

$Y = 3$ {Altitude}

out_context

$X = 8$ {Distance}

This modification of the debugger is accomplished by adding the following rule:

***Command(context), CurrentContext(C), Binds(C,N,V), Comment(S,C)**

$\Rightarrow \text{Display}(N \text{ ^{``} = `` ^{string} \leftarrow \text{int}[V] \text{ ^{``} \{ `` ^{S ^{``}} \}, E)$

else previous rule.

The reader should try to think of other possible runtime applications of comments and other nonprogram information.

3. Conditional Expressions

3.1 Concrete and Abstract Syntax

Next we introduce a conditional expression into our language. This construct will be necessary for effective use of the recursive functions introduced in Part IV. A conditional expression is displayed in the following format:

(if *B*
 then *T*
 else *F*)

In the context of a larger program it would look like this:

```
let N = (X-1)
  (if (N > 0)
    then 1
    else (N * (N - 1)) )
```

Note that we will also have to extend our operator application syntax to include relational operators ('= ', '> ', etc.); this is left as an exercise for the reader.

The abstract structure of conditional expressions is represented by the following relations:

- **ConEx(E)**

E is a conditional expression

Degree(ConEx,1).

- Cond(B, E)

B is the condition of E

Function(Cond, ConEx, expr).

- Conseq(T, E)

T is the consequent of E

Function(Conseq, ConEx, expr).

- Alt(F, E)

F is the alternate of E

Function(Alt, ConEx, expr).

3.2 Editor Commands

It's necessary to incorporate a new command into the editor so that we can create ConEx nodes.

The rule for the 'if' command is routine:

*Command(if), *CurrentNode(E), *Undef(E), *Avail(B, T, F)

\Rightarrow ConEx(E), Cond(B, E), Conseq(T, E), Alt(F, E),

Undef(B), Undef(T), Undef(F), CurrentNode(B).

The regularity of all these node creation commands (**if**, **let**, **var**, etc.) suggests that there ought to be a regular way of handling them. This too is left as an exercise for the reader.

The editor must also be augmented with rules for the **in**, **out**, **next** and **prev** commands on ConEx nodes. The reader should also consider how this proliferation of rules can be avoided. A typical rule is the **in** rule:

*Command(in), *CurrentNode(E), ConEx(E), Cond(B, E)

\Rightarrow CurrentNode(B), Command(show).

3.3 Unparsing

As usual we have two rules: analysis and synthesis. The analysis rule is:

$$*\text{Unparse}(E), \text{ConEx}(E), \text{Cond}(B,E), \text{Conseq}(T,E), \text{Alt}(F,E)$$

$$\Rightarrow \text{Unparse}(B), \text{Unparse}(T), \text{Unparse}(F).$$

The synthesis rule gathers the images of the subexpressions and assembles them into an image for the conditional:

$$\text{ConEx}(E), \text{Cond}(B,E), \text{Conseq}(T,E), \text{Alt}(F,E), *Image(U,B), *Image(V,T), *Image(W,F)$$

$$\Rightarrow \text{Image}(\text{TabIn} \wedge \text{NL} \wedge$$

$$“(\text{if} \text{ ”} \wedge U \wedge \text{NL} \wedge$$

$$“ \text{ then } ” \wedge V \wedge \text{NL} \wedge$$

$$“ \text{ else } ” \wedge W \wedge “) ” \wedge$$

$$\text{TabOut} \wedge \text{NL}, E).$$

A rule for commented ConEx nodes is left as an exercise for the reader.

3.4 Evaluation

Evaluation of the conditional node requires two separate analysis/synthesis steps. The first analysis rule requests evaluation of the condition:

$$*\text{Eval}(E,C), \text{ConEx}(E), \text{Cond}(B,E)$$

$$\Rightarrow \text{Eval}(B,C).$$

When a value is returned for the condition, either the consequent or the alternate must be evaluated (depending on whether or not the condition was **true**). Thus the synthesis pass for the condition is combined with the analysis pass for either the consequent or alternate. Evaluation of the consequent when the condition is true is handled by this rule:

$$\text{ConEx}(E), \text{Cond}(B,E), \text{Conseq}(T,E), *Value(\text{true}, B, C)$$

$$\Rightarrow \text{Eval}(T,C).$$

Evaluation of the alternate is analogous.

The final synthesis pass occurs when a value arrives at either the consequent or alternate; this value is attached to the conditional itself. The case where the value arrives at the consequent is handled by:

$$\text{ConEx}(E), \text{Conseq}(T, E), * \text{Value}(V, T, C)$$
$$\Rightarrow \text{Value}(V, E, C).$$

The alternate case is analogous.

4. References

- [MacLennan83] MacLennan, B. J., A View of Object-Oriented Programming, Naval Postgraduate School Computer Science Department Technical Report NPS52-83-001, February 1983.
- [MacLennan84] MacLennan, B. J., The Four Forms of Ω : Alternate Syntactic Forms for an Object-Oriented Language, Naval Postgraduate School Computer Science Department Technical Report NPS52-84-026, December 1984.
- [MacLennan85a] MacLennan, B. J., A Simple Software Environment Based on Objects and Relations, *Proc. of ACM SIGPLAN 85 Conf. on Language Issues in Prog. Environments*, June 25-28, 1985, and Naval Postgraduate School Computer Science Department Technical Report NPS52-85-005, April 1985.
- [MacLennan85b] MacLennan, B. J., Experience with Ω : Implementation of a Prototype Programming Environment Part I, Naval Postgraduate School Computer Science Department Technical Report NPS52-85-006, May 1985.
- [MacLennan85c] MacLennan, B. J., Experience with Ω : Implementation of a Prototype Programming Environment Part II, Naval Postgraduate School Computer Science Department Technical Report NPS52-85-015, December 1985.
- [McArthur84] McArthur, Heinz M., *Design and Implementation of an Object-Oriented, Production-Rule Interpreter*, MS Thesis, Naval Postgraduate School Computer Science Department, December 1984.
- [Ufford85] Ufford, Robert P., *The Design and Analysis of a Stylized Natural Grammar for an Object Oriented Language (Omega)*, MS Thesis, Naval Postgraduate School Computer Science Department, June 1985.

APPENDIX A: Prototype Programming Environment

The following is a loadable input file for the prototype programming environment described in this report. It is accepted by the McArthur interpreter [McArthur84], which differs in a few details from the Ω notation used in this report (see [MacLennan84]). Also note that the declarations have been reordered somewhat from that in previous reports in this series; the new order better reflects the object-oriented design. A transcript of a test execution of this environment is listed in Appendix B.

```
! _____  
!  
!          PI-3  
!  
!  
! A simple programming environment for an arithmetic  
! expression language, including interpreter, unparser,  
! syntax directed editor and debugger.  
!  
! Features included in the language:  
!  
! - Constants  
!  
! - Arithmetic Operations  
!  
! - Statically Nested Declarations  
!  
! - Comments  
!  
! - Conditional Expressions  
!  
! _____  
!  
! PERVASIVE RELATIONS  
!  
! Evaluation  
  
newrelation {"Eval"};  
newrelation {"Check"};  
newrelation {"Value"};  
newrelation {"Meaning"};
```


newrelation {"Explanation"};

! Contexts and Bindings

newrelation {"Context"};

newrelation {"Binds"};

newrelation {"Nonlocal"};

newrelation {"Looking"}.

! Unparsing

newrelation {"Unparse"};

newrelation {"Image"};

newrelation {"Template"};

! Comments

newrelation {"Comment"}.

! Format Control Constants

define {root, "NL", "
"};

define {root, "TabIn", " "};

define {root, "TabOut", " "};

! Logical Constants

define {root, "true", 1};

define {root, "false", 0}.

! COMMAND INTERPRETER

! Command Interpreter Relations

newrelation {"Command"};

newrelation {"Argument"};

newrelation {"Root"};

newrelation {"Undef"};

newrelation {"CurrentNode"};

newrelation {"CurrentContext"};

newrelation {"SuspendedEval"};

newrelation {"Break"};

newrelation {"EvalPending"};

newrelation {"ShowPending"};

newrelation {"CommandPending"};

newrelation {"CreateRoot"};

newrelation {"CreateContext"}.

define {root, "ComIntRules", < <

! evaluate Command

if *Command("evaluate"), CurrentNode(E), CurrentContext(C)

-> Eval(E.C), EvalPending(E), CommandPending(E);

if *Value(V,E,C), *EvalPending(E), *CommandPending(-)

-> displayn {V};

! Error Handler

if *Break(M,E,C), *CommandPending(-), *EvalPending(R), *SuspendedEval(-)

```

-> displayn{M}, SuspendedEval(R), CurrentNode(E), CurrentContext(C);

! resume Command

if *Command("resume"), SuspendedEval(Nil)

-> displayn{"no evaluation in progress"}

else if *Command("resume"), CurrentNode(E), CurrentContext(C), *SuspendedEval(R)

-> Eval(E,C), EvalPending(R), SuspendedEval(Nil);

! return Command

if *Command("val"). *Argument(V), CurrentNode(E)

-> Value(V,E,C);

! show Command

if *Command("show"), CurrentNode(E)

-> Unparse(E), ShowPending(E), CommandPending(E);

if *Image(S,E), *ShowPending(E), *CommandPending(-)

-> displayn{S};

! abort Command

if Command("abort"), *Eval(E,C) -> ;

if Command("abort"), *Value(V,E,C) -> ;

if Command("abort"), *Check(V,E,C) -> ;

if Command("abort"), *Nonlocal(C,D) -> ;

if Command("abort"), *Binds(D,N,V) -> ;

if *Command("abort"),

```

```

      ^Eval(E,C), ^Value(V,E,C), ^Nonlocal(C,D), ^Binds(D,N,V),
      *SuspendedEval(- ), *CurrentContext(- )
-> CurrentContext(Nil), SuspendedEval(Nil), displayn{"aborted"};

! done Command

if *Command("done") -> displayn{"PI system stopped"};

```

! Syntax Directed Editing

```
if *Command("delete"), CurrentNode(E), Undef(E)
```

```
-> displayn("already deleted");
```

! begin Command

```
if *Command("begin"), *CurrentNode(Q)
```

```
-> CreateRoot(newobj{}), CommandPending(Nil);
```

```
if *CreateRoot(E), *CommandPending(- )
```

```
-> Root(E). Undef(E). CurrentNode(E);
```

! root Command

```
if *Command("root"), *CurrentNode(Q), Root(E)
```

```
-> CurrentNode(E), Command("show");
```

! Debugging Commands

! context Command

```
if *Command("context"), CurrentContext(C), Binds(C,N,V), Comment(S,C)
```

```
-> displayn( N + " = " + int_str V + " {" + S + "}" )
```

```
else if *Command("context"), CurrentContext(C), Binds(C,N,V)
```

```
-> displayn( N + " = " + int_str V )
```

```
else if *Command("context")
```

```
-> displayn("no bindings");
```

! out_context Command

```
if *Command("out_context"), *CurrentContext(D), Nonlocal(C,D)
```

```

-> CurrentContext(C), Command("context")

else if *Command("out_context")

-> displayn ("at outermost level");

! in_context Command

if *Command("in_context"), *CurrentContext(C), Nonlocal(C,D)

-> CurrentContext(D), Command("context")

else if *Command("in_context")

-> displayn("at innermost level");

! alter Command

if *Command("alter"), *Argument(U),

    CurrentContext(C), *Binds(C.N,V)

-> Binds(C,N,U), Command("context")

else if *Command("alter"), *Argument(Q)

-> displayn("no binding");

> > }.

act {ComIntRules}.

```

! COMMENTS

```
define {root, "RemRules", < <
```

```
! rem Command
```

```
if *Command("rem"), *Argument(S), CurrentNode(E), ~Comment(-,E)
```

```
-> Comment(S,E);
```

```
if *Command("rem"), *Argument(-), CurrentNode(E), Comment(-,E)
```

```
-> displayn("node already commented");
```

```
! delete_rem Command
```

```
if *Command("delete_rem"), CurrentNode(E), *Comment(-,E)
```

```
-> displayn("done");
```

```
if *Command("delete_rem"), CurrentNode(E), ~Comment(-,E)
```

```
-> displayn("no comment");
```

```
> > }.
```

```
act {RemRules}.
```

! INCOMPLETE PROGRAM

```
! Tables
```

```
Explanation ("incomplete program", ["error", 0]).
```

```
define {root, "IncomProgRules", < <
```

```
! Evaluation
```

```
if *Eval(E,C), Undef(E), *CurrentNode(Q)
```

```
-> Break("Incomplete", E, C);
```


! Unparsing

if *Unparse(E), Undef(E)

-> Image ("< expr> ", E);

> > }.

act {IncomProgRules}.

! CONSTANT NODES

! Relations

newrelation {"Con"};

newrelation {"Litval"}.

! Functions

fn Id [x]: x.

! Tables

Meaning (Id, "lit").

Template (int_str, "lit").

define {root, "ConRules", < <

! Evaluation

if *Eval(e,c), Con(e), Litval(v,e), Meaning(f, "lit")

-> Value(f[v], e, c);

! Unparsing

if *Unparse(e), Con(e), Litval(v,e), Template(f, "lit"), Comment(s,e)

-> Image(f[v] + " {" + s + "}", e)

else if *Unparse(e), Con(e), Litval(v,e), Template(f, "lit")

-> Image(f v , e);

! # Command

if *Command("#"), *Argument(V), IsInt V , CurrentNode(E), *Undef(E)

-> Con(E), Litval(V,E);

```
if *Command("#"), *Argument(V), CurrentNode(E), ~Undef(E)
```

```
-> displayn("defined node");
```

```
! delete Command
```

```
if *Command("delete"), CurrentNode(E), *Con(E), *Litval(V,E)
```

```
-> Undef(E), Command("show");
```

```
> > }.
```

```
act {ConRules}.
```

! VARIABLE NODES

! Relations

```
newrelation {"Var"};
```

```
newrelation {"Ident"}.
```

```
define {root, "VarRules", < <
```

! Evaluation

```
if *Eval(E.C), Var(E), Ident(N,E)
```

```
-> Looking(N,C,E,C):
```

```
if *Looking(N,C,E,D), Binds(C,N.V)
```

```
-> Value(V,E,D)
```

```
else if *Looking(N,C,E.D), Nonlocal(Cprime,C)
```

```
-> Looking(N,Cprime,E,D)
```

```
else if *Looking(N,C,E.D), *CurrentNode(Q), *CurrentContext(Q)
```

```
-> Break("Unbound: " + N, E, D);
```

! Unparsing

```
if *Unparse(E), Var(E), Ident(N,E), Comment(S,E)
```

```
-> Image( N + " {" + S + "}", E)
```

```
else if *Unparse(E), Var(E), Ident(N,E)
```

```
-> Image(N,E);
```

! var Command

```
if *Command("var"), *Argument(N), CurrentNode(E), *Undef(E)
```

```
-> Var(E), Ident(N,E);
```

! delete Command

if *Command("delete"), CurrentNode(E), *Var(E), *Ident(N,E)

-> Undef(E), Command("show");

> > }.

act {VarRules}.

! APPLICATION NODES

! Relations

```
newrelation {"Appl"};
newrelation {"Op"};
newrelation {"Left"};
newrelation {"Right"};

newrelation {"Create Appl"}.
```

! Evaluation Functions

```
fn Sum [x,y]: x + y;
fn Dif [x,y]: x - y;
fn Product [x,y]: x * y;
fn Quotient [x,y]:
  if y = 0 -> "error", 1
  else x / y;
fn Equal [x,y]: if x = y -> true else false;

fn IsErrorcode [w]:
  if ~IsList[w] | w = Nil -> Nil
  else first[w] = "error";
```

! Unparsing Functions

```
fn upSum [x,y]: "(" + x + " + " + y + ")";
fn upDif [x,y]: "(" + x + " - " + y + ")";
fn upProd [x,y]: "(" + x + " x " + y + ")";
fn upQuot [x,y]: "(" + x + " / " + y + ")";
fn upEqua [x,y]: "(" + x + " = " + y + ")";
```

! Evaluation Tables

Meaning (Sum, "+ ");

Meaning (Dif, "-");

Meaning (Product, "x");

Meaning (Quotient, "/");

Meaning (Equal, "=").

! Unparsing Tables

Template (upSum, "+ ");

Template (upDif, "-");

Template (upProd, "x");

Template (upQuot, "/");

Template (upEqua, "=").

! Other Tables

Explanation ("division by zero", ["error", 1]).

define {root, "ApplRules", < <

! Evaluation

if *Eval(e,c), Appl(e), Left(x.e), Right(y,e)

-> Eval(x,c), Eval(y,c);

if *Value(u,x,c), *Value(v,y,c),

Appl(e), Op(n,e), Left(x,e), Right(y,e), Meaning(f, n)

-> Check(f.u,v], e. c);

if *Check(w, e, c), ~IsErrorcode|w|

-> Value(w, e. c);


```
if *Check(w, e, c), IsErrorcode[w], Explanation(s, w), *CurrentNode(q)
```

```
-> Break(s, e, c);
```

```
! Unparsing
```

```
if *Unparse(e), Appl(e), Left(x,e), Right(y,e)
```

```
-> Unparse(x), Unparse(y);
```

```
! Unparsing Comments on Applications
```

```
if Appl(E), Op(N,E), Left(X,E), Right(Y,E),
```

```
  *Image(U,X), *Image(V,Y), Comment(S,E)
```

```
-> Image( " {" + S + " } (" + U + N + V + ") ", E)
```

```
else if *Image(u,x), *Image(v,y),
```

```
  Appl(e), Op(n,e), Left(x,e), Right(y,e), Template(f, n)
```

```
-> Image(f[u,v], e);
```

```
! +, -, x, /, = Commands
```

```
if *Command(op), member [op, "+", "-", "x", "/", "="],
```

```
  *CurrentNode(E), *Undef(E)
```

```
-> CommandPending(E), CreateAppl(op, E, newobj{}, newobj{});
```

```
if *CreateAppl(op,E,X,Y), *CommandPending(E)
```

```
-> {Appl(E), Op(op,E), Left(X,E), Right(Y,E),
```

```
  Undef(X), Undef(Y), CurrentNode(X);
```

```
  Command("show");
```

```
! delete Command
```

```
if *Command("delete"), CurrentNode(E),
```

```
  *Appl(E), *Op(N,E), *Left(X,E), Right(Y,E)
```

```

-> Undef(E), Command("show");

! in Command

if *Command("in"), *CurrentNode(E), Left(X,E)

-> CurrentNode(X), Command("show");

! out Command

if *Command("out"), *CurrentNode(X), Left(X,E)

-> CurrentNode(E), Command("show");

if *Command("out"), *CurrentNode(Y), Right(Y,E)

-> CurrentNode(E), Command("show");

! next Command

if *Command("next"), *CurrentNode(X), Left(X,E), Right(Y,E)

-> CurrentNode(Y), Command("show");

! prev Command

if *Command("prev"), *CurrentNode(Y), Right(Y,E), Left(X,E)

-> CurrentNode(X), Command("show");

> > }.

act{ApplRules}.

```

! BLOCK

! Relations

newrelation {"Block"};

newrelation {"BndVar"};

newrelation {"BndVal"};

newrelation {"Body"};

newrelation {"CreateLet"}.

define {root, "BlockRules", < <

! Evaluation

if *Eval(E,C), Block(E), BndVal(X,E)

-> Eval(X,C);

if Block(E), BndVar(N,E), BndVal(X,E), Body(B,E),

*Value(V,X,C), Comment(S,E)

-> CreateContext (newobj{}, N, V, C, B, S)

else if Block(E), BndVar(N,E), BndVal(X,E), Body(B,E),

*Value(V,X,C)

-> CreateContext (newobj{}, N, V, C, B);

if *CreateContext(D,N,V,C,B,S) -> CreateContext(D,N,V,C,B), Comment(S,D);

if *CreateContext(D,N,V,C,B)

-> Context(D), Binds(D,N,V), Nonlocal(C,D), Eval(B.D);

if Block(E), Body(B,E),

*Value(V,B,D), *Nonlocal(C,D), *Binds(D,N,W), *Context(D)

-> Value(V,E,C);

! Unparsing

if *Unparse(E), Block(E), BndVal(X,E), Body(B,E)

-> Unparse(X), Unparse(B);

! Unparsing comments on blocks

if Block(E), BndVar(N,E), BndVal(X,E), Body(B,E),

*Image(U,X), *Image(V,B), Comment(S,E)

-> Image(

TabIn + NL + "let {" + S + "}"

+ TabIn + NL + N + "= " + U

+ NL + V + "}"

+ TabOut + TabOut, E)

else if Block(E), BndVar(N,E), BndVal(X,E), Body(B,E),

*Image(U,X), *Image(V,B)

-> Image(TabIn + NL

+ "let " + N + "= " + U

+ TabIn + NL + V + "}"

+ TabOut + TabOut,

E);

! let Command

if *Command("let"), *Argument(N), *CurrentNode(E), *Undef(E)

-> CommandPending(E), CreateLet(N, E, newobj{}, newobj{});

if *CreateLet (N, E, X, B), *CommandPending(E)

{Block(E), BndVar(N,E), BndVal(X,E), Body(B,E),

Undef(X), Undef(B), CurrentNode(X);

Command("show");

! in Command

if *Command('in'), *CurrentNode(E), BndVal(X,E)

-> CurrentNode(X), Command('show');

! out Command

if *Command('out'), *CurrentNode(X), BndVal(X,E)

-> CurrentNode(E), Command('show');

if *Command('out'), *CurrentNode(B), Body(B,E)

-> CurrentNode(E), Command('show');

! next Command

if *Command('next'), *CurrentNode(X),

BndVal(X,E), Body(B,E)

-> CurrentNode(B), Command('show');

! prev Command

if *Command('prev'), *CurrentNode(B),

Body(B,E), BndVal(X,E)

-> CurrentNode(X), Command('show');

> > }.

act {BlockRules}.

! CONDITIONAL EXPRESSION NODES

! Relations

```
newrelation {"ConEx"};
```

```
newrelation {"Cond"};
```

```
newrelation {"Conseq"};
```

```
newrelation {"Alt"};
```

```
newrelation {"CreateConEx"}.
```

```
define {root, "ConExRules", < <
```

! Evaluation

```
if *Eval(E,C), ConEx(E), Cond(B,E)
```

```
-> Eval(B,C);
```

```
if ConEx(E), Cond(B,E), Conseq(T,E), *Value(true,B,C)
```

```
-> Eval(T,C);
```

```
if ConEx(E), Cond(B,E), Alt(F,E), *Value(false,B,C)
```

```
-> Eval(F,C);
```

```
if ConEx(E), Conseq(T,E), *Value(V,T,C)
```

```
-> Value(V,E,C);
```

```
if ConEx(E), Alt(F,E), *Value(V,F,C)
```

```
-> Value(V,E,C);
```

! Unparsing

```
if *Unparse(E), ConEx(E), Cond(B,E), Conseq(T,E), Alt(F,E)
```

```
-> Unparse(B), Unparse(T), Unparse(F);
```

if ConEx(E), Cond(B,E), Conseq(T,E), Alt(F,E),

 *Image(U,B), *Image(V,T), *Image(W,F)

-> Image(TabIn + NL +

 "(If " + U + NL +

 "then " + V + NL +

 "else " + W + ")" +

 TabOut + NL, E);

! Editing

! if Command

if *Command("if"), *CurrentNode(E), *Undef(E)

-> CommandPending(E), CreateConEx(E, newobj{}, newobj{}, newobj{});

if *CreateConEx(E,B,T,F), *CommandPending(E)

-> {ConEx(E), Cond(B,E), Conseq(T,E), Alt(F,E).

 Undef(B), Undef(T), Undef(F), CurrentNode(B);

 Command("show");

! in Command

if *Command("in"), *CurrentNode(E), ConEx(E), Cond(B,E)

-> CurrentNode(B), Command("show");

! out Command

if *Command("out"), *CurrentNode(B), Cond(B,E), ConEx(E)

-> CurrentNode(E), Command("show");

if *Command("out"), *CurrentNode(T), Conseq(T,E), ConEx(E)

-> CurrentNode(E), Command("show");


```

if *Command("out"), *CurrentNode(F), Alt(F,E), ConEx(E)
-> CurrentNode(E), Command("show");

! next Command

if *Command("next"), *CurrentNode(B), Cond(B,E), Conseq(T,E)
-> CurrentNode(T), Command("show");

if *Command("next"), *CurrentNode(T), Conseq(T,E), Alt(F,E)
-> CurrentNode(F), Command("show");

! prev Command

if *Command("prev"), *CurrentNode(F), Alt(F,E), Conseq(T,E)
-> CurrentNode(T), Command("show");

if *Command("prev"), *CurrentNode(T), Conseq(T,E), Cond(B,E)
-> CurrentNode(B), Command("show");

> > }.

act {ConExRules}.

```

! TEST DRIVER

! Relations

```
newrelation {"Script"};
```

```
newrelation {"Test"}.
```

! Monadic Command List

```
define {root, "MonadicCommands",  
  {"#", "val", "let", "var", "alter", "rem"}}.
```

```
define {root, "TestRules", <<
```

! Script Sequencer

```
if *Script(A,Nil), ~Command(-), ~CommandPending(-)
```

```
-> A("Script completed")
```

```
else if *Script(A,L), ~Command(-), ~CommandPending(-),
```

```
  member [first[L], MonadicCommands]
```

```
-> { display {" ... "};
```

```
    display {first | rest [L]};
```

```
    displayn {" " + first [L]};
```

```
    Command(first[L]), Argument(first|rest[L]);
```

```
    Script(A, rest|rest[L]) }
```

```
else if *Script(A,L),
```

```
  ~Command(-), ~CommandPending(-)
```

```
-> { displayn {" ... " + first [L]};
```

```
    Command(first[L]);
```

```
    Script(A, rest[L]) };
```

! Test Scripts

```
if *Test(A,1) -> {  
  Script{[  
    "begin","rem","Distance","let","X","+","#",3,"next","#",5,"out","next",  
    "rem","Altitude","let","Y","/","#",6,"next","#",2,"out","next",  
    "+","var","X","next","rem","offset","/","var","Y","next","#",1,  
    "root","evaluate"]};  
  A("Test done");  
};
```

```
if *Test(A,2) -> {  
  Script{["in","next","in","next","in","next","in","next",  
    "delete"."rem","error!","#",0,"root","evaluate"]};  
  A("Test done");  
};
```

```
if *Test(A,3) -> {  
  Script{["context","out_context","alter",7,  
    "in_context","out_context","out_context","abort","show"]};  
  A("Test done");  
};
```

```
if *Test(A,4) -> {  
  Script{["delete","if","=","var","Y","next","#",0,"out","next",  
    "#",1,"next","=","var","X","next","#",1,"root","evaluate"]};  
  A("Test done");  
}
```

```
>>> }.
```

act {TestRules}.

! Initialize Data Structures

CurrentNode(Nil).

CurrentContext(Nil).

SuspendedEval(Nil).

displayn{"PI-3 System loaded"}.

APPENDIX B: Transcript of Ω Session

The following is a transcript of an Ω session illustrating the operation of the prototype programming environment shown in Appendix A. The assertion 'Script {testscript}' causes the commands in testscript to be executed in order. The n th testscript is executed by 'Test{n}'. Each command is printed on a separate line, followed by whatever output is generated by the programming environment. This transcript was produced by the McArthur interpreter [McArthur84].

% omega

OMEGA-1 11/30/84

Use Cntl-D or exit{} to quit.

For help, enter help{"?"}.

To report a bug, enter Bugs{}.

newrelation rule activated.

> do{"PI3.rul"}.

PI-3 System loaded

OK

> {Test{1}; Test{2}; Test{3}; Test{4}; Script{"done"}}.

... begin

... Distance rem

... X let

< expr>

... +

< expr>

... 3 #

... next

< expr>

... 5 #

... out
 (3 + 5)
 ... next
 < expr>
 ... Altitude rem
 ... Y let
 < expr>
 ... /
 < expr>
 ... 6 #
 ... next
 < expr>
 ... 2 #
 ... out
 (6 / 2)
 ... next
 < expr>
 ... +
 < expr>
 ... X var
 ... next
 < expr>
 ... offset rem
 ... /
 < expr>
 ... Y var
 ... next
 < expr>

... 1 #

... root

[let {Distance}

X = (3 + 5)

[let {Altitude}

Y = (6 / 2)

(X + {offset} (Y/1))]]

... evaluate

11

... in

(3 + 5)

... next

[let {Altitude}

Y = (6 / 2)

(X + {offset} (Y/1))]

... in

(6 / 2)

... next

(X + {offset} (Y/1))

... in

X

... next

{offset} (Y/1)

... in

Y

... next

1

... delete

< expr>

... error! rem

... 0 #

... root

[let {Distance}

X = (3 + 5)

[let {Altitude}

Y = (6 / 2)

(X + {offset} (Y/0 {error!})))]]

... evaluate

division by zero

... context

Y = 3 {Altitude}

... out_context

X = 8 {Distance}

... 7 alter

X = 7 {Distance}

... in_context

Y = 3 {Altitude}

... out_context

X = 7 {Distance}

... out_context

no bindings

... abort

aborted

... show

{offset} (Y/0 {error!})

.. delete

< expr>

... if

< expr>

... =

< expr>

... Y var

... next

< expr>

... 0 #

... out

(Y = 0)

... next

< expr>

... 1 #

... next

< expr>

... -

< expr>

... X var

... next

< expr>

... 1 #

... root

| let {Distance}

X = (3 + 5)

| let {Altitude}

Y = (6 / 2)

(X +

(If (Y = 0)

then 1

else (X - 1))

)]]

... evaluate

15

... done

PI system stopped

OK

> exit {}.

Goodbye.

%

INITIAL DISTRIBUTION LIST

Defense Technical Information Center Cameron Station Alexandria, VA 22314	2
Dudley Knox Library Code 0142 Naval Postgraduate School Monterey, CA 93943	2
Office of Research Administration Code 012 Naval Postgraduate School Monterey, CA 93943	1
Chairman, Code 52 Department of Computer Science Naval Postgraduate School Monterey, CA 93943	40
Associate Professor Bruce J. MacLennan Code 52ML Department of Computer Science Naval Postgraduate School Monterey, CA 93943	12
Dr. Robert Grafton Code 433 Office of Naval Research 800 N. Quincy Arlington, VA 22217-5000	1
Dr. David Mizell Office of Naval Research 1030 East Green Street Pasadena, CA 91106	1
Dr. Stephen Squires DARPA Information Processing Techniques Office 1400 Wilson Boulevard Arlington, VA 22209	1
Professor Jack M. Wozencraft, 62Wz Department of Electrical and Comp. Engr. Naval Postgraduate School Monterey, CA 93943	1
Professor Rudolf Bayer Institut für Informatik Technische Universität Postfach 202420 D-8000 Munchen 2 West Germany	1

Dr. Robert M. Balzer USC Information Sciences Inst. 4676 Admiralty Way Suite 10001 Marina del Rey, CA 90291	1
Mr. Ronald E. Joy Honeywell, Inc. Computer Sciences Center 10701 Lyndale Avenue South Bloomington, MI 55402	1
Mr. Ron Laborde INMOS Whitefriars Lewins Mead Bristol Great Britain	1
Mr. Lynwood Sutton Code 424, Building 600 Naval Ocean Systems Center San Diego, CA 92152	1
Mr. Jeffrey Dean Advanced Information and Decision Systems 201 San Antonio Circle, Suite 286 Mountain View, CA 94040	1
Mr. Jack Fried Mail Station D01/31T Grumman Aerospace Corporation Bethpage, NY 11714	1
Mr. Dennis Hall New York Videotext 104 Fifth Avenue, Second Floor New York, NY 10011	1
Professor S. Ceri Laboratorio di Calcolatori Dipartimento di Elettronica Politecnico di Milano 20133 - Milano Italy	1
Mr. A. Dain Samples Computer Science Division - EECS University of California at Berkeley Berkeley, CA 94720	1
Antonio Corradi Dipartimento di Elettronica Informatica e Sistemistica Universita Degli Studi di Bologna Viale Risorgimento, 2	

Bologna Italy	1
Dr. Peter J. Welcher Mathematics Dept., Stop 9E U.S. Naval Academy Annapolis, MD 21402	1
Dr. John Goodenough Wang Institute Tyng Road Tyngsboro, MA 01879	1
Professor Richard N. Taylor Computer Science Department University of California at Irvine Irvine, CA 92717	1
Dr. Mayer Schwartz Computer Research Laboratory MS 50-662 Tektronix, Inc. Post Office Box 500 Beaverton, OR 97077	1
Professor Lori A. Clarke Computer and Information Sciences Department LGRES ROOM A305 University of Massachusetts Amherst, MA 01003	1
Professor Peter Henderson Department of Computer Science SUNY at Stony Brook Stony Brook, NY 11794	1
Dr. Mark Moriconi SRI International 333 Ravenswood Avenue Menlo Park, CA 95025	1
Professor William Waite Department of Electrical and Computer Engineering The University of Colorado Campus Box 425 Boulder, CO 80309-0425	1
Professor Mary Shaw Software Engineering Institute Carnegie-Mellon University Pittsburgh, PA 15213	1
Dr. Warren Teitelman Engineering/Software Sun Microsystems Federal, Inc. 2550 Garcia Avenue	

Mountain View, CA 94031

DUDLEY KNOX LIBRARY



3 2768 00337455 4